



PRODUCT RANGE

- 1. Under-Floor Heating Systems:
- Heating Mats
- Heating Cable Sections
- Ultra Thin Aluminium Foil Heating Mats
- 2. Thermostats
- 3. Under-Carpet Heaters
- 4. Heating Carpets
- 5. Towel Heaters
- 6. Mirror De-Misters
- 7. Mold Prevention System





Over 1 Million Installations in Russia




UNDER-FLOOR HEATING ADVANTAGES

- Entire Room Area Heating
- > Comfortable, Natural Heat Distribution
- No Air Convection Flows
- > Affordable: Up to 70% Savings on Power Bills
- > Hypo-Allergic: No Dust/Allergens in Air
- > Healthy: No Oxygen Burned; No Moisture
- > Flexible Settings: New Projects and Renovations
- Designer Friendly: Does Not Occupy Room Space
- Safe: EMR level less than 0.2 mkTl







YOUR BEST FRIEND IN WINTER!....



ELECTRIC UNDER-FLOOR HEATING ADVANTAGES



- Simple and Fast Installation: No Plumbing **Contractor Needed, One Connection to the Power**
- **Less Ceiling Height Sacrifice**
- Affordable Installation:
- No need for heat pump or mini-boiler
- Materials getting cheaper every year
- **Installation Flexibility:**
- Into the Mortar Screed
- Into the Tile Glue
- **Under the Carpeted/Wood/Parquet Floors**
- No Maintenance Needed

ice-cold floors...



PROFI / TROPIX DOUBLE CORE HEATING MATS

Self-adhesive heating mat with perfect cable laying radius developed for fast and easy installation in standard layout premises

TECHNICAL DATA


Rated Power	230 VAC
Specific Power	100/150/200 W/m ²
Mat Width	0.5 m
Heating Area, m ²	up to 20
Cable Diameter	Approx. 3.5-5.0 mm
Cold Lead Length	3 m


CERTIFICATIONS





RoHS







TLBE / GB DOUBLE CORE HEATING CABLE

Flexible solution for complex configuration premises

TECHNICAL DATA


Rated Power	230 VAC
Specific Power	16 to 18 W/m
Heating Area, m ²	up to 22
Minimum Bending Radius	30 mm
Cable Diameter	3.5 to 7.9 mm
Cold Lead Length	3 m

CERTIFICATIONS





RoHS









ALUMIA ULTRA-THIN FOILED HEATING MATS

1.8 mm thick heating mat for installation in the floor floating layer

TECHNICAL DATA

Rated Power	230 VAC
Specific Power	80/150 W/m ²
Mat Width	0.5 m
Heating Area, m ²	up to 15
Cable Diameter	Approx. I.18 to 1.62 mm
Cold Lead Length	3 to 4 m

CERTIFICATIONS










THERMOSTATS PRODUCT RANGE

- Programmable:
- ✓ MSC 350 WiFi Smartphone Controlled
- ✓ SE 200 Touch Screen
- ✓ Warmstad 520 AIR. Heat Saver
- Reliable and Versatile:
- ✓ Warmstad 515. Master of Heat Precision
- ✓ Warmstad 510. Heat Management Classic














THERMOSTATS SPECIFICATIONS

	MCS 350	SE 200	TP 520 AIR	TP515	TP 510
Power Supply Voltage	230 VAC				
Maximum Load Current, A	16 A				
Power Consumption, W	5	0.45	0.45	0.45	0.45
Programmable	4 events/7 days	4 events/7 days	4 events/7 days	-	-
Weight, g	160	160	110	110	100
Dimensions, mm	90×90×40	90×90×40	86×86×42	86×86×42	86×88×36
Safety Rating	IP2 I	IP21	IP2 I	IP2 I	IP21
Safety Class	II	II	II	II	II
Remote Floor Temperature Sensor, kOhm	6.8; 10; 12; 15; 33; 47	6.8	6.8; 10; 12; 15; 33; 47	6.8; 10; 12; 15; 33; 47	6.8
Sensor Cold Lead Length	2 m	2 m	2 m	2 m	2 m
Warranty	2 years				
Settings Memory w/o Power	I2 months	12 months	10 years	10 years	-



PROGRAMMABLE THERMOSTATS' POWER SAVING PRINCIPLE





EXPRESSUNDER-CARPET HEATER

- √ Safe and reliable heater
- ✓ Suitable for all types of premises and flooring
- ✓ Portable, easy to clean

Dimensions, m	2.0x1.4	2.8x1.8		
Area, m ²	2.8	5.04		
Power, W	330	610		
Surface Temperature, °C	30			
Power Supply Voltage	230 VAC			
Protection Class / Protection Rating	II / IPX7			
Cold Lead Length, m	2.5			
Warranty	2 years			








HEATING CARPET

- ✓ Delicate shoe drying and feet warming
- ✓ Can be used for simultaneous drying of up to 5 pairs of shoes
- √ Compact and portable

Dimensions, cm	80x50	90x60		
Area, m ²	0.4	0.54		
Power, W	70			
Surface Temperature, °C	35-40			
Power Supply Voltage	230 VAC			
Protection Class / Protection Rating	I / IP67			
Cold Lead Length, m	1.8			
Warranty	2 years			







FLORA TOWEL HEATER

- \checkmark Up to 40% more efficient than metal towel rails
- ✓ Independent from water supply, heating or plumbing
- √ 16 design styles

Dimensions, cm	60x60	90x60	
Area, m²	0.36	0.54	
Power, W	160	260	
Weight with rails, kg	5.2	10.5	
Surface Temperature, °C	65-75		
Power Supply Voltage	230 VAC		
Protection Class / Protection Rating	II / IP44		
Cold Lead Length, m	2		
Warranty	2 years		







MIRROR DE-MISTER

- ✓ Adhesive film for easy instant installation
- ✓ Equipped with heat insulation
- ✓ Can be plugged into the mirror's backlight or main power system

Dimensions, cm	50x42	50x60	
Area, m ²	0.21	0.3	
Power, W	35	50	
Surface Temperature, °C	18-30		
Power Supply Voltage	230 VAC		
Protection Class / Protection Rating	I / IPX4		
Cold Lead Length, m	1.5		
Warranty	2 years		







DR. DRYMAN MOISTURE DESICCANT

- ✓ Eliminates dampness which causes mold and mildew formation
- ✓ Creates comfortable and healthy microclimate
- ✓ Does not occupy valuable life space and is interior neutral
- ✓ High efficiency and effectiveness

Dimensions, cm	10x25	10x40	10x65	
Area, m²	0.25	0.4	0.6	
Power, W	75	125	195	
Power Supply Voltage	230 VAC			
Cold Lead Length, m	1.5			









Thank You for Your Attention!



<u>www.avalio.shop</u> +357 9971 0826